

Sales promotion



KEL-VERA UR 1-2-3 175/400

- Equipment for grinding wheel left, 500 x 80 mm
- Equipment for grinding wheel right, 500 x 80 mm
- Semi-automatic balancing unit KEL-BALANCE for universal wheelheads
- Supplementary materials for semi-automatic balancing unit KEL-BALANCE for universal wheelheads
- Operating unit for one high frequency internal grinding spindle MFM
- High frequency internal grinding spindle MFM 1224/42
- Internal grinding quill HJND 21-1645
- Standard workhead with C-axis
- Lower part of workhead with fine and rough adjustment
- Backlash free driving flange
- Standard tailstock with combined, manual and hydraulic sleeve retraction
- Lower part of tailstock with micro-adjustment
- Three-jaw chuck, spiral type, size 160 mm
- Arrangement for Arobotech steady rest
- Arrangement for CBN dressing roll
- Arrangement for high frequency dressing device on upper table, for rotary dressing tools, for external grinding wheels
- Active flagging KEL-POS, Marposs T25G, mounted on wheelhead, swivel angle 52°
- KEL-SET tool measuring system for CNC control GRINDplusIT
- Basic modul for KEL-TOUCH contact sensor and KEL-BALANCE automatic balancing device for CNC control GRINDplusIT
- KEL-TOUCH, wheel and workpiece contact sensor, for universal wheelheads R / RS / UR / URS
- KEL-TOUCH, mounted on the wheelhead
- Arrangement for measuring control units Movomatic ES124 or Marposs P5
- Arrangement for connection of a central cooling unit, 10 bar
- Full machine enclosure - emulsion
- Mist collector - emulsion
- Electrical driving unit for sliding door for CNC control GRINDplusIT
- Service unit for pneumatic auxiliary functions

L. KELLENBERGER & Co. AG

Heiligkreuzstrasse 28
9009 St.Gallen / Schweiz
Telefon +41 (0)71 242 91 11
Telefax +41 (0)71 242 92 22

www.kellenberger.com
info@kellenberger.net